



pavlik laminating

# Quote Request

## One Side Lamination

Company Name: \_\_\_\_\_

Contact Name: \_\_\_\_\_

Email: \_\_\_\_\_

Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

Sheet Size to Us: \_\_\_\_\_ " x \_\_\_\_\_ "

Image Area: \_\_\_\_\_ " x \_\_\_\_\_ "

*\*WE NEED, AT LEAST 1/2" ALL THE WAY AROUND THE PERIMETER OF THE PRESS SHEET, BEYOND THE IMAGE\**

Paper Weight: \_\_\_\_\_

(lb. or point thickness)

*\*MUST MIC OUT TO AT LEAST 5 PT. THICK, WITH A MAXIMUM THICKNESS OF 24 PT.\**

Paper Type:  Bond/Text/Book

Cover/Index

Other: \_\_\_\_\_

Paper Coating:

Coated one side

Coated two sides

Uncoated

Type of Ink:

Offset Press

Indigo

Other Digital Color Copier (Please Specify): \_\_\_\_\_

4/4 OR  4/0

Quantity:

Single Original

OR

Multiple Originals

Quantity of sheets: \_\_\_\_\_

How Many: \_\_\_\_\_ Quantity of Each: \_\_\_\_\_

Collated:

Quantity of Sets: \_\_\_\_\_ Sheets per Set: \_\_\_\_\_

*\*IF YOU WANT SEPARATOR SHEETS, THEY MUST BE THE SAME STOCK AS THE JOB AND MUST BE LAMINATED. YOU WILL BE CHARGED FOR THEM! IF THE STOCK IS DIFFERENT, THEY WILL HAVE TO BE REMOVED. YOU WILL BE CHARGED TO REMOVE AND/OR REINSERT!\**

Film Type:

Polyester

Polypropylene

Nylon/Curl Free

Film Finish

Gloss

Matte (Please Specify: "soft touch", Scuff Resistant, etc.): \_\_\_\_\_

Other (Please Specify): \_\_\_\_\_

Laminate one side

OR

Laminate TWO SIDES

Project Notes/Special Instructions:

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_